Raw product fact sheet



Introduction

The option to finish your own floor is yours with Raw.



Core MaterialPlantation Eucalyptus PlyPlantation Eucalyptus PlyCore MaterialIntense brush textureSubtle brush textureSurface FeatureIntense brush textureRusticAppearanceRusticRusticLamella Wear Layer4mm2mmCertificate Of OriginYesYesOverall Thickness15mm12mmWidth189mm190mmLengthup to 1830mmup to 2100mmWeight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor Heating plywood over concreteWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	FEATURE	ELEGANT OAK	PREMIÈRE OAK
Surface FeatureIntense brush textureSubtle brush textureAppearanceRusticRusticLamella Wear Layer4mm2mmCertificate Of OriginYesYesOverall Thickness15mm12mmWidth189mm190mmLengthup to 1830mmup to 2100mmWeight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesInstall OverWood, concrete, plywood & plywood over concreteWood, over concrete	Species	Genuine French Oak	Genuine French Oak
AppearanceRusticRusticAppearanceRusticRusticLamella Wear Layer4mm2mmCertificate Of OriginYesYesOverall Thickness15mm12mmWidth189mm190mmLengthup to 1830mmup to 2100mmWeight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesInstall OverWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Core Material	Plantation Eucalyptus Ply	Plantation Eucalyptus Ply
Lamella Wear Layer4mm2mmCertificate Of OriginYesYesOverall Thickness15mm12mmWidth189mm190mmLengthup to 1830mmup to 2100mmWeight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall Sui-Floor HeatingYesYesWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Surface Feature	Intense brush texture	Subtle brush texture
Certificate Of OriginYesYesOverall Thickness15mm12mmWidth189mm190mmLengthup to 1830mmup to 2100mmWeight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Appearance	Rustic	Rustic
Overall Thickness15mm12mmWidth189mm190mmLengthup to 1830mmup to 2100mmWeight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall OverWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Lamella Wear Layer	4mm	2mm
Width189mm190mmLengthup to 1830mmup to 2100mmWeight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall OverWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Certificate Of Origin	Yes	Yes
Lengthup to 1830mmup to 2100mmWeight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Overall Thickness	15mm	12mm
Weight667kg/m³ or 22kg/carton667kg/m³ or 20kg/cartonCoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesInstall OverWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Width	189mm	190mm
CoatingGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGerman UV cured Acrylic Lacquer incorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesInstall OverWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Length	up to 1830mm	up to 2100mm
incorporating Anti-Scratch technologyincorporating Anti-Scratch technologyGlossUltra MattUltra MattPack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesInstall OverWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Weight	667kg/m ³ or 22kg/carton	667kg/m ³ or 20kg/carton
Pack Size2.075m²/carton2.394m²/cartonEdge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesInstall OverWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Coating	, ,	, ,
Edge ProfileSlightly BevelSlightly BevelProfileTongue & GrooveTongue & GrooveInstall SuitabilityFloating, direct glued, staples & nailed downFloating, direct glued, staples & nailed downInstall Sub-Floor HeatingYesYesInstall OverWood, concrete, plywood & plywood over concreteWood, concrete, plywood & plywood over concrete	Gloss	Ultra Matt	Ultra Matt
Profile Tongue & Groove Tongue & Groove Install Suitability Floating, direct glued, staples & nailed down Floating, direct glued, staples & nailed down Install Sub-Floor Heating Yes Yes Install Over Wood, concrete, plywood & plywood over concrete Wood, concrete, plywood & plywood over concrete	Pack Size	2.075m ² /carton	2.394m ² /carton
Install Suitability Floating, direct glued, staples & nailed down Floating, direct glued, staples & nailed down Install Sub-Floor Heating Yes Yes Install Over Wood, concrete, plywood & plywood over concrete Wood, concrete, plywood & plywood over concrete	Edge Profile	Slightly Bevel	Slightly Bevel
Install Sub-Floor Heating Yes Yes Install Over Wood, concrete, plywood & plywood over concrete Wood, concrete, plywood & plywood over concrete	Profile	Tongue & Groove	Tongue & Groove
Install Over Wood, concrete, plywood & Wood, concrete, plywood & plywood over concrete plywood over concrete	Install Suitability	Floating, direct glued, staples & nailed down	Floating, direct glued, staples & nailed down
plywood over concrete plywood over concrete	Install Sub-Floor Heating	Yes	Yes
Colour Match Accessories Aluminium trims & MDF wrapped scotia Aluminium trims & MDF wrapped scotia	Install Over		
	Colour Match Accessories	Aluminium trims & MDF wrapped scotia	Aluminium trims & MDF wrapped scotia