



Cherry Mahogany

PRODUCT FACT SHEET

Introduction


A limited edition species that has a subtle red to blush undertone, Cherry Mahogany is a high density hardwood that shows an interesting gum vein features, which combined with its tight interlocking grain makes it a species that is sought after. Growing in the coastal regions of New South Wales, Cherry Mahogany is a large Australian hardwood that grows to around 35 metres in height.

Species in Detail

COMMON NAMES	Cherry Mahogany
LOOK & FEATURES	Tight interlocking grain pattern with interesting veins and features
BOTANICAL NAME	Corymbia Gummifera
COLOUR	Subtle red through to blush
DRY DENSITY	900kg/m ³
NATURAL DURABILITY	Class 1 (above ground)

Species Hardness Ratings

TASMANIAN OAK	4.9
FRENCH OAK	6.0
AMERICAN WHITE OAK	6.0
GREENTREE ROSE	7.0
FLOODED GUM	7.5
GREENTREE BLONDE	7.5
NORTHERN BEECH	8.0
TALLOWOOD	8.6
CHERRY MAHOGANY	8.8
SILVERTOP STRINGYBARK	8.8
SYDNEY BLUE GUM	9.0
BLACKBUTT	9.1
NEW ENGLAND BLACKBUTT	9.2
BRUSH BOX	9.5
WHITE MAHOGANY	10.0
SPOTTED GUM	11.0
TURPENTINE	12.0
RED MAHOGANY	12.0
FOREST RED GUM	12.0
RED IRONBARK	14.0
GREY IRONBARK	14.0
GREY GUM	14.0
GREY BOX	15.0



Species hardness is measured in Janka numbers - the higher the number, the harder the species.

Grade Descriptions

SELECT GRADE: The features that are present in Select Grade flooring are relatively small and few in number, and although they are visible the features do not dominate the appearance of the floor.

STANDARD GRADE (Medium Feature): Flooring in this grade will be moderately featured. Gum veins, gum pockets, insect trails, burls and borer holes are some of the characteristics that will be more prevalent in Standard Grade.

FEATURE GRADE (High Feature): Feature Grade flooring is heavily peppered with natural features, particularly large gum veins.

RUSTIC GRADE: A full featured floor to provide an old world charm. It may contain features that are more prominent than Feature Grade but with the structural integrity of a Feature Grade floor.



Product Matrix

PRODUCT	WIDTHS	THICKNESS	PLYWOOD	PARTICLEBOARD	BATTENS	BEARERS & JOIST
Ultra10 <small>Ultra 10mm thickness</small>	86mm	10mm, 12mm	✓	✓		
OVERLAY	83mm	14mm	✓	✓		
FOURTEEN <small>Fourteen 14mm thickness</small>	130mm, 180mm	14mm	✓	✓		
TRADITIONAL FLOORING	80mm, 130mm	19mm	✓	✓	✓	✓
WIDEBOARD FLOORING	180mm	21mm	✓	✓	✓	✓

Boards wider than 80mm in traditional flooring should be top nailed as per AS1684.